

DATASHEET

802.11g High Power Industrial Hotspot™ RLX2-IHG

The ProSoft Technology 802.11g High Power Industrial Hotspot™ (RLX2-IHG) is a high-speed wireless Ethernet radio for long range applications. The RLX2-IHG uses the 2.4 GHz band and supports a data rate up to 54Mbps. The Hotspot supports Access Point, Repeater, Bridging, and Client modes. The RLX2-IHG offers fast roaming, hazardous location certifications, as well as vibration and shock resistance.

The included IH Browser configuration and monitoring software allows viewing network topology, assigning IP addresses, monitoring network diagnostics, and updating radio firmware. The OPC Diagnostic Server is ideal for managing long range wireless SCADA networks.



| Features | Benefits |
|---|--|
| 802.11b and g Access Point, Bridge, Repeater, and Client modes in one radio | ◆ All-in-one radio supports long range applications in the 2.4 GHz spread spectrum bands (fully compatible with RLXIB-IHG networks) |
| High transmit power; industrial operating temperatures; vibration and shock resistant | ◆ Supports long distance while being dependable in critical control systems and extreme environments |
| Fast Roaming (less than 50 ms) with Full Bridging | ◆ Maintains seamless, high speed connections to one or more devices on moving equipment and machines (such as cranes, AGVs, and carriers) as they travel between Access Points |
| IGMP Snooping & Packet Filtering | ◆ Optimizes UDP multicast traffic for superior EtherNet/IP I/O communications |
| 802.11i, WPA2, and 128-bit AES encryption | ◆ Ensures secure networking with advanced authentication and encryption |
| 12/24 VDC and PoE power options | ◆ Support for common industrial power sources or use Power over Ethernet (PoE) to reduce cabling costs |
| Built-in Serial Device Server | ◆ Wirelessly connect serial (Modbus, DNP 3, etc.) devices over 802.11 wireless networks |
| Built-in Web Server | ◆ Simple local and remote configuration, monitoring, and wireless network diagnostics |
| IH Browser Software Utility | ◆ Centralized configuration and remote management of Industrial Hotspot networks |
| Disaster recovery feature (microSD) | ◆ Quick field replacement without need of programming software or operator training |

Specifications

Radio

| | |
|--|--|
| Frequency Band (Varies by country) | 802.11g: 2.412 GHz to 2.462 GHz (FCC) 2.412 GHz to 2.472 GHz (ETSI) |
| Wireless Standards | 802.11b, 802.11g, 802.11i |
| Transmit Power (Programmable) (varies by country) | Up to 24 dBm (250 mW) |
| Channel Data Rates (Modulation) | 802.11g: (OFDM) Mbps 54, 48, 36, 24, 18, 12, 9, and 6 802.11b: (DSS) Mbps 11, 5.5, 2, and 1 |
| Receiver Sensitivity (Typical) | -94 dBm @ 1 Mbps -92 dBm @ 11 Mbps -84 dBm @ 24 Mbps -72 dBm @ 54 Mbps |
| Channel Selection | 802.11g: 1 to 11 (FCC), 1 to 13 (ETSI) |
| Security | WPA2 - 802.11i with 128 bit AES-CCM Legacy WPA TKIP, WEP support MAC ID filter, Admin password |

Physical

| | |
|----------------|---|
| Enclosure | Extruded aluminum with DIN and panel mount |
| Size | 14.8 x 11.8 x 3.8 cm (H x W x D) 5.82 x 4.64 x 1.48 in (H x W x D) |
| Shock | IEC 60068 2-6 (20 g, 3-Axis) |
| Vibration | IEC 60068 2-27 (5 g, 10 Hz to 150 Hz) |
| Ethernet Ports | (1) 10/100/1000 Base-T, RJ45 connector |
| Serial Port | (1) DB9 female (serial tunneling & encapsulation) |
| Antenna Port | (1) RP-SMA connector |
| Weight | 1.1 lbs (499g) |

Environmental

| | |
|------------------------|-------------------------------------|
| Operating Temperature | -40°C to +75°C (-40°F to +167°F) |
| Humidity | Up to 100% RH, with no condensation |
| External Power | 10 VDC to 24 VDC |
| Power over Ethernet | 802.3af Compliant |
| Peak Power Consumption | < 7W |

Regulatory Approvals

Wireless Approvals

Visit our web site at www.prosoft-technology.com for current wireless approval information.

Hazardous Locations

UL/cUL; Class 1, Div 2

Ex Certificate (ATEX Directive, Zone 2)

Regulatory

CSA/CB Safety

CE Mark

FCC/IC

ETSI

What's Included in the Box:

- (1) RLX2-IHG (802.11g High Power Industrial Hotspot)
- (1) A2502S-OA (2 dBi omni-directional stub antenna)
- (1) Industrial-class microSD card with default configuration loaded
- (1) Power Connector Plug (for connection to customer's DC power source wiring)
- (1) Power connector wire insertion tool
- (1) Product Support DVD



Additional Products

ProSoft Technology® offers a full complement of hardware and software solutions for a wide variety of industrial communication platforms. For a complete list of products, visit our web site at: www.prosoft-technology.com

Ordering Information

To order this product, please use the following:

802.11g High Power Industrial Hotspot™

RLX2-IHG-A

Includes: Radio, stub antenna, Power Connector Plug, microSD card, and Support DVD

Optional Accessories

Bench Test Kit

RLX-IHBTK

Includes: 115/230 VAC bench power supply, Ethernet and serial cables

To place an order, please contact a local ProSoft distributor.

A list of ProSoft-authorized distributors is available on our website at:

www.prosoft-technology.com.

From the main menu, select Distributors and the Country for region-specific information.

Copyright © 2013 ProSoft Technology, Inc., all rights reserved. 1/31/2013

Specifications subject to change without notice.